



**UNIVERSITI PUTRA MALAYSIA**

***NUMERICAL SIMULATION OF MIXING CHARACTERISTICS OF  
CNG-AIR MIXER FOR DUAL-FUEL VEHICLE***

**HASSAN SADAH MUHSSEN**

**FK 2016 146**



**NUMERICAL SIMULATION OF MIXING CHARACTERISTICS OF  
CNG-AIR MIXER FOR DUAL-FUEL VEHICLE**

**By**

**HASSAN SADAH MUHSSEN**

**Thesis Submitted to the School of Graduate Studies, Universiti Putra Malaysia,  
in Fulfilment of the Requirements for the Degree of Master of Science**

**November 2016**

## **COPYRIGHT**

All material contained within the thesis, including without limitation text, logos, icons, photographs and all other artwork, is copyright material of Universiti Putra Malaysia unless otherwise stated. Use may be made of any material contained within the thesis for non-commercial purposes from the copyright holder. Commercial use of material may only be made with the express, prior, written permission of Universiti Putra Malaysia.

Copyright © Universiti Putra Malaysia



**DEDICATED**

*My dear father, Sadah Muhssen,*

*My beloved mother, Ibtisam Khayoon,*

*My loving wife, Zainab Atiyah,*

*Faithful brothers, sisters, children, relatives, & friends*





Abstract of thesis presented to the Senate of Universiti Putra Malaysia in fulfillment of the requirement for the degree of Master of Science

## **NUMERICAL SIMULATION OF MIXING CHARACTERISTICS OF CNG-AIR MIXER FOR DUAL-FUEL VEHICLE**

By

**HASSAN SADAH MUHSSEN**

**November 2016**

**Chairman : Siti Ujila Masuri, PhD**  
**Faculty : Engineering**

A compressed natural gas (CNG)-air mixer is a device like a carburettor positioned at the air intake manifold of the engine to mix CNG with incoming air at proper amounts of CNG and air prior to entering the combustion chamber. According to literature, the best design of CNG-air mixer is one that is able to meet the conditions of 1) supply the engine with a homogeneous mixture of CNG and air, 2) with air and CNG with the required air fuel ratio (AFR), and 3) without reduction of the air intake manifold size. The homogeneous mixture occurs when the uniformity index (UI) of methane mass fraction ( $M_{\text{CH}_4}$ ) =1.0. From previous studies, there is no design of CNG-air mixer which could satisfy all the above three conditions at the same time.

This research carried out a computational fluid dynamics (CFD) study to design a CNG-air mixer for CNG-diesel dual fuel (DDF) engine. The objectives of this study were to examine the performance of existing Secondary Fuel Premixing Controller (SFPMC) commercial mixer and modify it in terms of air fuel ratio (AFR) and CNG-air mixture homogeneity (CAMH).

The validity and reliability procedures of the simulation results were carried out using the grid independent test, and verification by comparing the results with the literature.

Results from simulation indicated that the original mixer (model 1) was unable to control AFR due to the shaft design of the control valve. Furthermore, this mixer could not provide a homogeneous mixture of CNG and air due to the mixer's internal

design, position and directions of the CNG holes. Therefore, the mixer design was modified in terms of AFR and CNG-air mixture homogeneity. Design modification of the control valve shaft was the first method to control AFR, while the second modification involved removing the control valve and also assuming that the gas flow rate is controlled by the electronic flow controller and electronic control unit (ECU). For the mixture homogeneity, there were 10 alternative designs that were tested (models 2-11) to achieve the desired design. The uniformity index (UI) of methane mass fraction ( $M_{\text{Ch}_4}$ ) was the approach used to quantify CNG spread on the mixer outlet. The UI of  $M_{\text{Ch}_4}$  represents how  $M_{\text{Ch}_4}$  varies over a plane surface, where a value of 0 and 1 indicate the lowest and highest uniformity of gas spread, respectively. Based on the results obtained from mixer models 1-11, it can be concluded that models 8 and 11 showed a superior performance in terms of UI. The minimum UI of  $M_{\text{Ch}_4}$  at the outlet of these two mixer models was not less than 0.96 at various engine speeds of 1000, 1500, 2000, 3000, and 3600 rpm, and 0.87 at various AFRs of 10, 17.2, 20, 30, and 40. On the other hand, at the outlet of original mixer, the maximum UI of  $M_{\text{Ch}_4}$  was not higher than 0.57 at various engine speeds, and 0.58 at various AFRs. In terms of AFR, the optimized mixer with a new control valve shaft showed better controlling of AFR at the various engine speeds compared with the original mixer.

Abstrak tesis yang dikemukakan kepada Senat Universiti Putra Malaysia sebagai memenuhi keperluan untuk ijazah Sarjana Sains

**SIMULASI BERANGKA CIRI-AM MENCAMPUR PENGADUN CNG-UDARA UNTUK KENDERAAN DWI-BAHAN BAKAR**

Oleh

**HASSAN SADAH MUHSSEN**

**November 2016**

**Pengerusi : Siti Ujila Masuri, PhD**  
**Fakulti : Kejuruteraan**

Pengadun gas asli termampat (CNG)-udara adalah alat seperti karburetor yang diletakkan di pancarongga pengambilan udara enjin untuk mencampur CNG dengan udara masuk pada jumlah CNG dan udara yang sesuai sebelum memasuki kebuk pembakaran. Menurut literatur, reka bentuk yang paling sesuai untuk pengadun CNG-udara adalah sesuatu yang dapat memenuhi syarat-syarat 1) membekalkan enjin dengan campuran homogen CNG dan udara, 2) dengan udara dan CNG pada nisbah udara bahan bakar yang diperlukan (AFR), dan 3) tanpa pengurangan saiz pancarongga pengambilan udara. Campuran yang homogen berlaku apabila indeks keseragaman (UI) bagi pecahan jisim metana ( $M_{CH_4}$ ) = 1.0. Dari kajian sebelum ini, tidak ada reka bentuk pengadun CNG-udara yang boleh memenuhi kesemua tiga-tiga syarat di atas secara serentak.

Kajian ini adalah satu kajian menggunakan pengkomputeran dinamik bendalir (CFD) untuk mereka-bentuk pengadun CNG-udara bagi enjin CNG-diesel dwi-bahan bakar (DDF). Objektif kajian ini adalah untuk mengkaji prestasi pengadun dagangan Pengawal Pra-Adunan Bahan Bakar Sekunder yang sedia ada dan mengubahsuainya dari segi nisbah udara bahan bakar (AFR) dan kehomogenan campuran CNG-udara (CAMH).

Prosedur kesahan dan kebolehpercayaan bagi keputusan simulasi telah dijalankan menggunakan grid ujian bebas, dan penentusahan oleh perbandingan keputusan dengan literatur.

Keputusan daripada simulasi menunjukkan bahawa pengadun asal (model 1) tidak dapat mengawal AFR disebabkan oleh reka bentuk shaf injap kawalan yang tidak

sesuai. Tambahan pula, pengadun ini tidak dapat menyediakan campuran homogen CNG dan udara disebabkan oleh reka bentuk dalaman, kedudukan dan arah lubang CNG. Oleh itu, reka bentuk pengadun telah diubahsuai dari segi AFR dan kehomogenan campuran CNG-udara. Pengubahsuaian reka bentuk shaf injap kawalan adalah kaedah pertama untuk mengawal AFR, manakala pengubahsuaian kedua melibatkan mengeluarkan injap kawalan dan juga menganggap bahawa kadar aliran gas dikawal oleh pengawal elektronik aliran serta unit kawalan elektronik (ECU). Untuk kehomogenan campuran, terdapat 10 reka bentuk alternatif yang diuji (model 2-11) untuk mencapai reka bentuk yang dikehendaki. Indeks keseragaman (UI) bagi pecahan jisim metana ( $M_{Ch4}$ ) adalah pendekatan yang digunakan untuk mengukur agihan CNG pada saluran keluar pengadun. UI  $M_{Ch4}$  mewakili bagaimana  $M_{Ch4}$  berbeza agihannya di atas sesuatu permukaan, yang mana nilai 0 dan 1 masing-masing menunjukkan keseragaman bagi penyebaran gas yang paling rendah dan paling tinggi. Berdasarkan keputusan yang diperolehi daripada model pengadun 1-11, dapat disimpulkan bahawa model 8 dan 11 menunjukkan prestasi yang lebih baik dari segi UI. UI minimum  $M_{Ch4}$  di saluran keluar kedua-dua model pengadun tersebut tidak kurang daripada 0.96 pada pelbagai kelajuan enjin di paras 1000, 1500, 2000, 3000, dan 3600 rpm, dan 0.87 di pelbagai AFRs iaitu 10, 17.2, 20, 30, dan 40. Sebaliknya, di saluran keluar pengadun asal, UI maksimum  $M_{Ch4}$  tidak melebihi 0.57 pada pelbagai kelajuan enjin, dan 0.58 pada pelbagai AFRs. Dari segi AFR, pengadun yang dioptimumkan dengan shaf injap kawalan baru menunjukkan pengawalan AFR yang lebih baik pada pelbagai kelajuan enjin berbanding dengan pengadun asal.

## ACKNOWLEDGEMENTS

Praise to Allah S.W.T for giving me the health, patience, knowledge, and blessing that led to the successful completion of this study.

First and foremost, I would like to express my deep gratitude to my supervisor, Dr. Siti Ujila Binti Masuri for her guidance, invaluable advice, constructive comments, and suggestions to complete my research successfully. My sincere appreciation is also extended to the supervisory committee members, Prof. Ir. Dr. Barkawi Bin Sahari and Dr. Abdul Aziz Bin Hairuddin for their guidance, advice, suggestions, and support given throughout my study.

Secondly, I would like to thank Universiti Putra Malaysia for the facilities and I am grateful to my beloved country (Iraq), Ministry of Higher Education, for the financial support. In addition, this work was also supported by UPM Grant Scheme with Reference Number: GP-IPB-2013-9412900 and was carried out in Universiti Putra Malaysia (UPM). Therefore, I would like to acknowledge their support with gratitude.

Finally, deepest thanks and appreciation to my parents, wife, brothers, sisters, children, and others for their cooperation, encouragement, constructive suggestion, and support for the report completion, from the beginning till the end. Also thanks to all of my friends and everyone, who contributed by supporting my work and helped me during these two years of thesis preparation.

I certify that a Thesis Examination Committee has met on 21 November 2016 to conduct the final examination of Hassan Sadah Muhssen on his thesis entitled "Numerical Simulation of Mixing Characteristics of CNG-Air Mixer for Dual-Fuel Vehicle" in accordance with the Universities and University Colleges Act 1971 and the Constitution of the Universiti Putra Malaysia [P.U.(A) 106] 15 March 1998. The Committee recommends that the student be awarded the Master of Science.

Members of the Thesis Examination Committee were as follows:

**Mohd Idris Shah bin Ismail, PhD**

Senior Lecturer  
Faculty of Engineering  
Universiti Putra Malaysia  
(Chairman)

**Nor Mariah binti Adam, PhD**

Associate Professor Ir.  
Faculty of Engineering  
Universiti Putra Malaysia  
(Internal Examiner)

**Mazlan Abdul Wahid, PhD**

Associate Professor  
Universiti Teknologi Malaysia  
Malaysia  
(External Examiner)



---

**NOR AINI AB. SHUKOR, PhD**

Professor and Deputy Dean  
School of Graduate Studies  
Universiti Putra Malaysia

Date: 26 January 2017

This thesis was submitted to the Senate of Universiti Putra Malaysia and has been accepted as fulfilment of the requirements for the degree of Master of Science. The members of the Supervisory Committee were as follows:

**Siti Ujila Binti Masuri, PhD**

Senior Lecturer

Faculty of Engineering

Universiti Putra Malaysia

(Chairman)

**Barkawi Bin Sahari, PhD**

Professor, Ir

Faculty of Engineering

Universiti Putra Malaysia

(Member)

**Abdul Aziz Bin Hairuddin, PhD**

Senior Lecturer

Faculty of Engineering

Universiti Putra Malaysia

(Member)

---

**ROBIAH BINTI YUNUS, PhD**

Professor and Dean

School of Graduate Studies

Universiti Putra Malaysia

Date:

## Declaration by graduate student

I hereby confirm that:

- this thesis is my original work;
- quotations, illustrations and citations have been duly acknowledged;
- ownership of intellectual property from the thesis is as stipulated in the Memorandum of Agreement (MoA), or as according to the Universiti Putra Malaysia (Research) Rules 2012, in the event where the MoA is absent;
- permission from supervisor and the office of Deputy Vice-Chancellor (Research and Innovation) are required prior to publishing it (in the form of written, printed or in electronic form) including books, journals, modules, proceedings, popular writings, seminar papers, manuscripts, posters, reports, lecture notes, learning modules or any other materials as stated in the Universiti Putra Malaysia (Research) Rules 2012;
- there is no plagiarism or data falsification/fabrication in the thesis, and scholarly integrity is upheld as according to the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) and the Universiti Putra Malaysia (Research) Rules 2012. The thesis has undergone plagiarism detection software.

Signature: \_\_\_\_\_ Date: \_\_\_\_\_

Name and Matric No.: Hassan Sadah Muhssen (GS39557)



## Declaration by Members of Supervisory Committee

This is to confirm that:

- the research conducted and writing of this thesis was under our supervision;
- Supervision responsibilities as stated in the Universiti Putra Malaysia (Graduate Studies) Rules 2003 (Revision 2012-2013) are adhered to.

Signature: \_\_\_\_\_  
Name of Chairman  
of Supervisory  
Committee: Siti Ujila Binti Masuri, PhD

Signature: \_\_\_\_\_  
Name of Member  
of Supervisory  
Committee: Barkawi Bin Sahari, PhD

Signature: \_\_\_\_\_  
Name of Member  
of Supervisory  
Committee: Abdul Aziz Bin Hairuddin, PhD

## TABLE OF CONTENTS

	Page
<b>ABSTRACT</b>	i
<b>ABSTRAK</b>	iii
<b>ACKNOWLEDGEMENTS</b>	v
<b>APPROVAL</b>	vi
<b>DECLARATION</b>	viii
<b>LIST OF TABLES</b>	xii
<b>LIST OF FIGURES</b>	xiv
<b>LIST OF APPENDICES</b>	xx
<b>LIST OF ABBREVIATIONS</b>	xxi
 <b>CHAPTER</b>	
 <b>1 INTRODUCTION</b>	 1
1.1 Background	1
1.2 Problem Statement	2
1.3 Objectives	2
1.4 Scope	3
1.5 Significance of research	3
1.6 Thesis Organization	3
 <b>2 LITERATURE REVIEW</b>	 5
2.1 Compressed Natural Gas (CNG) as an Alternative Fuel	5
2.1.1 Characteristics and Composition	5
2.1.2 Availability	6
2.1.3 Economic Aspect	6
2.1.4 Natural Gas Vehicles Growth and Worldwide Distribution	7
2.2 Engine Emission Types	7
2.3 Natural Gas-Diesel Dual Fuel	10
2.4 Air Fuel Ratio (AFR)	12
2.4.1 Effect of AFR on Engine Performance and Emissions	14
2.5 Effect of CNG-Air Mixture Homogeneity on the Engine Performance	18
2.6 Methods to Evaluate Mixture Homogeneity	23
2.6.1 Uniformity Index	24
2.6.2 Color Contours	24
2.6.3 Mass fraction	25
2.6.4 Quantity on Line	26
2.7 CNG-Air Mixer	26
2.7.1 Venturi mixer	26
2.7.2 Throttle Body Injection Mixer (TBIM)	35
2.7.3 Venturi Mixjector	36
2.7.4 CNG Premixing Controller	38

2.8	Computational Fluid Dynamics (CFD) Analysis	39
2.8.1	Introduction	39
2.8.2	Accuracy of CFD	40
2.9	Closure	41
<b>3</b>	<b>METHODOLOGY</b>	<b>43</b>
3.1	Introduction	43
3.2	Conceptual Design of Mixer	45
3.3	Procedure of Mixer Design	46
3.4	Verification	47
3.5	Computational Fluid Dynamics (CFD)	52
3.5.1	Mesh generation	52
3.5.2	Conservation Equations	57
3.5.3	Phenomena Simulated	60
3.5.4	ANSYS FLUENT solver setting	61
3.5.5	Segregate and Discretization	62
3.5.6	Residuals converging	62
3.5.7	Boundary conditions	63
3.5.8	Simulation Stages of the Mixer	65
<b>4</b>	<b>RESULTS AND DISCUSSION</b>	<b>75</b>
4.1	Calibration AND VERIFICATION	75
4.2	Performance Investigation of Original Mixer	78
4.2.1	Mixer design modification and test in terms of CNG-air mixture homogeneity	82
4.3	Design Optimization in Terms of AFR	115
4.3.1	Design modification to control the gas flow by control valve	115
4.3.2	Design modification assuming the gas flow is controlled by ECU	117
<b>5</b>	<b>CONCLUSION AND RECOMMENDATIONS</b>	<b>119</b>
5.1	Conclusion	119
5.2	Recommendations	120
	<b>REFERENCES</b>	<b>122</b>
	<b>APPENDICES</b>	<b>131</b>
	<b>BIODATA OF STUDENT</b>	<b>136</b>
	<b>LIST OF PUBLICATIONS</b>	<b>137</b>

## LIST OF TABLES

Table	Page
2.1: Physiochemical properties of CNG Vs gasoline and diesel (Dahake, Patil, & Patil, 2016; Khan et al., 2015b; Wei & Geng, 2016)	6
2.2: Various modeling capabilities and application areas of CFD (Hirsch, 2007; Versteeg & Malalasekera, 2007)	39
3.1: Engine specifications	47
3.2: Number of cells for each level for original mixer simulation	54
3.3: Air properties at the air inlet (FLUENT, 2012a; Ramasamy, 2006)	63
3.4: Methane properties (FLUENT, 2012a; Ramasamy, 2006)	65
4.1: Methane mass fraction results from literature and present CFD work	76
4.2: Flow stream lines, $M_{CH_4}$ at XY plane and outlet of original mixer (model 1) and mixer model 2	85
4.3: Flow stream lines, $M_{CH_4}$ color contours at XY plane and outlet of mixer models 3 and 4	86
4.4: Flow stream lines, $M_{CH_4}$ color contours at XY plane and outlet of mixer models 5 and 6	87
4.5: Flow stream lines, $M_{CH_4}$ color contours at XY plane and outlet of mixer models 7 and 8	88
4.6: Flow stream lines, $M_{CH_4}$ color contours at XY plane and outlet of mixer models 9 and 10	89
4.7: Flow stream lines, $M_{CH_4}$ color contours at XY plane and outlet of mixer models 8 and 11	90

4.8: Local $M_{\text{Ch}_4}$ color contour at the outlet of the original mixer (model 1) and 10 suggested mixers (models 2-11)	92
4.9: User-defined $M_{\text{Ch}_4}$ color contour at the outlet of the original mixer (model 1) and 10 suggested mixers (models 2-11)	94
4.10: Global $M_{\text{Ch}_4}$ color contours at the outlet of mixer models 1,8,11 with various engine speeds (1000, 1500, 2000, 3000, 3600 rpm)	97
4.11: Local $M_{\text{Ch}_4}$ color contours at the outlet of mixer models 1, 8, and 11 with various engine speeds (1000, 1500, 2000, 3000, 3600 rpm)	103
4.12: User define $M_{\text{Ch}_4}$ color contours at the outlet of mixer models 1,8,11 with various engine speeds (1000, 1500, 2000, 3000, 3600 rpm)	105
4.13: Global $M_{\text{Ch}_4}$ color contour at the outlet of mixer models 1, 8, and 11 with various AFRs (10, 17.2, 20, 30, and 40)	107
4.14: Local $M_{\text{Ch}_4}$ color contour at the outlet of mixer models 1, 8, and 11 with various AFRs (10, 17.2, 20, 30, and 40)	112
4.15: User-defined $M_{\text{Ch}_4}$ color contour at mixer outlet with various AFRs (10, 17.2, 20, 30, 40)	114

## LIST OF FIGURES

Figure	Page
2.1: Retail fuel prices (US \$) in top 15 CNG user countries (Khan et al., 2015b).	7
2.2: Emission benefit of CNG Vs Diesel and Gasoline (Khan et al., 2015a)	8
2.3: The relationship of diesel only and CNG-diesel emissions rate during variety of speeds (Jayaratne et al., 2010)	9
2.4: Comparison of NO <sub>x</sub> emission levels for dual fuel and diesel only modes (T. F. Yusaf et al., 2010)	9
2.5: Comparison of CO emission levels for dual fuel and diesel only modes (T. F. Yusaf et al., 2010)	10
2.6: Dual fuel engine conversion and gas fueling system (Jie Liu et al., 2013)	12
2.7: A/F ratio versus power (kW) (Saidur et al., 2007)	15
2.8: The effect of $\lambda$ value on the engine output torque, CH <sub>4</sub> emissions under, NO <sub>x</sub> emissions under various engine loads (Pang et al., 2013)	16
2.9: NG additional effect on bp for tested equivalence ratio range (Chaichan, 2014)	17
2.10: NG addition effect on UBHC and CO concentrations for tested equivalence ratio (Chaichan, 2014)	17
2.11: Variation of NO <sub>x</sub> with engine speed under maximum operating conditions (Talal Yusaf & Yusoff, 2000)	19
2.12: Power characteristics of the engine at maximum operation conditions (Talal Yusaf & Yusoff, 2000)	20
2.13: Power characteristics of the engine at different speeds (rpm) under full load condition (Supee, Shafeez, et al., 2014)	21

2.14: Nitric oxides ( $\text{NO}_x$ ) concentrations at different engine speeds under full load condition (Supee, Shafeez, et al., 2014)	21
2.15: CNG-air concentrations according to CNG injector position at the intake manifold (Supee, Mohsin, et al., 2014)	22
2.16: Power characteristics of the engine for different CNG injector position on intake manifold (Supee, Mohsin, et al., 2014)	23
2.17: Nitric Oxides ( $\text{NO}_x$ ) emissions of the engine for different injector position (Supee, Mohsin, et al., 2014)	23
2.18: Histogram of $M_{\text{ch4}}$ used to determine $M_{\text{hf}}$ (Chang et al., 2007)	25
2.19: Types of venture mixer (Ramasamy, 2006; Sera, Bakar, & Leong, 2003)	26
2.20: Power test results for different mixer designs (Sera et al., 2003)	27
2.21: Venturi mixer (Ramasamy, 2006)	28
2.22 Experiment and simulation results of AFR (Ramasamy, 2006)	28
2.23: $\text{CH}_4$ mass fraction color contour for mixer when the engine speeds are 1000 rpm, 4000 rpm, and 8000 rpm (Ramasamy, 2006)	29
2.24: Air-fuel ratio at different engine speeds (MM & MRM, 2008)	29
2.25: Methane mass fraction in the outlet of 12-hole mixer (Gorjibandpy & Sangsereki, 2010)	30
2.26: Contour of mass fraction of methane in 12-hole mixer (%) (Gorjibandpy & Sangsereki, 2010)	30
2.27: Schematic drawing of 8-hole venturi mixer (Talal Yusaf & Yusoff, 2000)	31
2.28: CNG concentration for 4-hole and 8-hole venturi mixer (Talal Yusaf & Yusoff, 2000)	31

2.29: High pressure CNG-air mixer (Noor et al., 2008)	32
2.30: Effect of changing the pressure on the AFR and flow behavior inside the mixer (Noor et al., 2008)	32
2.31: Effect of throat and jet diameters on the AFR and flow behavior inside the mixer (Noor et al., 2008)	33
2.32: Comparison between (a) first and (b) second generations of CNG-air mixer (Mohsin, Yaacob, & Y., 2008)	34
2.33: Throttle Body Injection Mixer (TBIM) (Chang et al., 2007)	35
2.34: Standardization of quality of homogeneity with (a) Grade A, (b) Grade B, (c) Grade C and (d) Grade D (Chang et al., 2007)	36
2.35: CNG-air concentrations in venturi mixjector (Supee, Shafeez, et al., 2014)	37
2.36: CNG-air pre mixing controller	38
2.37: Experimental and simulation pressure difference versus speed for mixer with 14 mm ring (Devarajan & Samykano, 2010)	41
2.38: Comparison of experiment and computation model results of the optimized design (Danardono et al., 2011)	41
3.1: Methodology flow chart of CNG-air mixer design	44
3.2: Parts of secondary fuel pre-mixing controller	46
3.3: Work principle and boundary conditions of mixer	46
3.4: CNG-air flow test rig (Ramasamy, 2006)	48
3.5: Dialog box of surface integral report of simulation static pressure result in ANSYS FLUENT	49



3.6: Steps of curve data extraction using Web Plot Digitizer software	51
3.7: Details of mesh at the wall	54
3.8: Mesh Levels analyzed	55
3.9: Methane mass fraction on the line (vertical diameter) at the outlet of original mixer for different mesh elements	56
3.10: Static pressure on the line(parallel to mixer axis) along the mixer for different mesh elements	56
3.11: Examlp of solving variables residuals converging achived in this resarch	63
3.12: Overall simulation stages done on the mixer	66
3.13: Original mixer with last position of control valve	67
3.14: Mixer models tested in terms of CNG-air mixture homogeneity	70
3.15: Steps of creating and setting up global color contours of $M_{\text{Ch}_4}$ at the mixer outlet	71
3.16: FLUENT steps of computing UI of $M_{\text{Ch}_4}$ at the mixer outlet	72
3.17: Original and two suggested control valves	74
4.1: New simulations and experiment pressure drop results along CNG-air mixer with various engine speeds	75
4.2: Results of methane mass fraction in the original mixer at engine speed of 1000 rpm	78
4.3: $M_{\text{Ch}_4}$ on the xy plane at the mid-section of original mixer (mode 1) when methane enters the mixer with atmospheric pressuire, and maximum flow rate at mixer outle at maximum engine speed (3600 rpm)	79

4.4: Total pressure on the xy plane at the mid-section of original mixer (model 1) when AFR is 17.2	80
4.5: $M_{Ch4}$ color contours and fluid flow stream lines of the original mixer (model 1) when AFR is 17.2	81
4.6: $M_{Ch4}$ color contours and fluid flow stream lines in original mixer (model 1) when methane inlet pressure is 0.25 MP	82
4.7: $M_{Ch4}$ Uniformity index at the outlet of original mixer (model 1) and models 2-11	91
4.8: Optimized mixers (a) with new design gas manifold, and new valve (cone shaft design), (b) with new design gas manifold, and without control valve	95
4.9: Relation between engine speed, out flow vlocity, and UI of $M_{Ch4}$ at the outlet of the original mixer (model 1) and mixer models 8 and 11	98
4.10: Fluid flow stream lines for the original and two developed mixers at the maximum engine speed (3600 rpm)	100
4.11: Fluid flow velocity vectors for the original and two developed mixers at the maximum engine speed (3600 rpm)	101
4.12: Relation between engine speed and variations between maximum and minimum $M_{Ch4}$ at the outlet of original mixer, mixer model 8 and mixer model 11	104
4.13: Relation between AFR, gas velocity at the gas holes, and UI of $M_{ch4}$ at the outlet of the original mixer (model 1), mixer model 8 and mixer model 11	108
4.14: Fluid flow stream lines from gas inlet to mixer outlet in mixer model 11, and these stream lines are colored by $M_{Ch4}$	110
4.15: Relation between AFR and VBMM $M_{Ch4}$ at the mixer outlet for the original mixer, mixer model 8 and mixer model 11	111

- 4.16: Relation between valve position (cm), engine speed (rpm), and AFR for original mixer (mode 1) and optimized mixer with valve (model 11) 116
- 4.17: AFR and CNG inlet mass flowrate with different engine speeds for mixer model 11 (optimized mixer without control valve) 118



## LIST OF APPENDICES

Appendix		Page
A	Technical Drawings	131
B	Verification Data	135



## LIST OF ABBREVIATIONS

(A/F)s	Stoichiometric air fuel ratio
Ø	Equivalence ratio
3D	Three dimensions
AFR	Air to fuel ratio
BDC	Bottom dead centre
CAMH	CNG-air mixture homogeneity
CAPMC	CNG-air pre mixing controller
CFD	Computational fluid dynamics
CI	Compression ignition engine
CNG	Compressed natural gas
CO	Carbon monoxide
CO <sub>2</sub>	Carbon dioxide
DDF	CNG-dual fuel diesel
ECU	Electronic control unit
GMSB	Gas Malaysia Sdn. Bhd.
HCAM	Homogeneous CNG-air mixture
HCNG	Hydrogen-compressed natural gas engine
L	Liter
L.H.V	Lower heating value
M <sub>ch4</sub>	Methane mass fraction
MDE	Dimethyl ether
mm	Millimeters
NG	Natural gas
NGVs	Natural gas vehicles
NMHC	Non-methane hydrocarbons
NO <sub>x</sub>	Nitrogen oxides
PM	Particulate matter
SFPMC	Secondary fuel pre mixing controller
SI	Spark ignition engine
SIMPLE	Semi-implicit method for pressure link equation
SPIT	Single point injection throttle
TBIM	Throttle body injection mixer
TCF	Trillion cubic feet
TDC	Top dead centre
UHC	Unburned hydrocarbon
UI	Uniformity index
λ	Relative air fuel ratio

# CHAPTER 1

## INTRODUCTION

### 1.1 Background

High thermal efficiency, durability, low carbon dioxide emission, reliability, high torque, and fuel economy are the factors that have made the diesel engines the preferred choice for passenger transport, trucks, and power generation operations (Chintala & Subramanian, 2013). In contrast, high localized temperature and combustion with heterogeneous air-fuel mixture have made the diesel engine produce a high level of nitrogen oxides emission and particulate matter emission (Chintala & Subramanian, 2013). Previous investigations have shown that people are prone to heart and lung diseases when exposed to exhaust particulate matter emission (Azad, Uddin, & Alam, 2012; Chintala & Subramanian, 2013). Many types of alternative fuels like alcohol, CNG, LPG, biogas, producer gas, and hydrogen were studied widely in the literature (Lata, Misra, & Medhekar, 2012). The factors such as high auto-ignition temperature, clean nature of combustion, and high availability at attractive prices make natural gas a good alternative fuel for diesel and gasoline engines (R. G. R. Papagiannakis et al., 2010). Compressed natural gas (CNG) is one of the natural gas forms, with some properties that make it an attractive alternative fuel for diesel fuel such as high octane number, high hydrogen to carbon rate, and leaner burn due to wide ignition limit (Kamil, Rahman, & Bakar, 2011).

Although CNG plays a significant role in reducing combustion emissions, the problems of high rate of  $\text{NO}_x$  and PM (particulate matter) emissions have been taken into account in recent times (T. F. Yusaf, Buttsworth, Saleh, & Yousif, 2010). CNG-diesel dual fuel (DDF) system has been developed to decrease  $\text{NO}_x$  and particulate matter emissions of diesel engines (Chintala & Subramanian, 2013; N. Kapilan, 2010; T Yusaf, Baker, Hamawand, & Noor, 2013). The work principle of the DDF engine is represented by the burning amount of the premixed CNG-air mixture by injecting a small amount of diesel “pilot” fuel inside the engine combustion chamber near the end of the compression stroke (Khan, Yasmin, & Shakoor, 2015b). CNG-air mixer is used to convert the diesel engine to DDF engine without more engine modifications. The main purpose of the mixer is to obtain a homogeneous mixture and suitable ratios of air and CNG as required by the engine (Abagnale et al., 2014; Chang, Yaacob, & Mohsin, 2007; Gorjibandpy & Sangsereki, 2010; Talal Yusaf & Yusoff, 2000). Venturi mixer, throttle body injection mixer (TBIM), venturi mixjector, and secondary fuel pre-mixing controller (SFPMC) are the devices that are used to mix the CNG and air prior to entering the engine combustion chamber.

All these mixing devices have been investigated extensively except the latter type, which is SFPMC. From the results of investigation of mixing devices except the

SFPMC, there was no mixer found that is optimized to provide a homogeneous CNG-air mixture (HCAM) at various engine speeds and various AFR without throttling engine air inlet. SFPMC mixer can be investigated and developed for a CNG-dual fuel diesel engine. Hence, this study focused on the modeling, testing and improving the mixing quality of CNG-air mixture in SFPMC mixer.

## 1.2 Problem Statement

All the CNG-air mixing devices like venturi mixer, venturi mixjector and throttle body injection mixer (TBIM) have been much investigated except the secondary fuel pre-mixing controller (SFPMC). The results of previous studies on the venturi showed a weakness in its performance in terms of CNG-air mixture homogeneity (CAMH) and AFR controlling at various engine speeds. In the venturi mixer the gas is rich at the wall regions and lean at the axial region; also the mixer should be long enough to provide homogenous mixture of CNG and air. Moreover, AFR is controlled by mixer design not as required by the engine due to stationary parts of the venturi mixer (MM & MRM, 2008; Mohsin, 2008; Ramasamy, 2006; T Yusaf et al., 2013; Talal Yusaf & Yusoff, 2000). For these two reasons, TBIM and venturi mixjector were the two suggested mixers to improve the CAMH and AFR controlling. TBIM is workable only with engine with throttle body and the CAMH depended on the butterfly valve position and gas injection frequency (Chang et al., 2007; Mohsin, 2008). On the other hand, venturi mixjector is a venturi mixer which uses electronic gas injectors to control AFR. Although this mixer controlled AFR and improved engine performance, but it is still venturi shaped which chokes the engine air intake. Moreover, CAMH occurs at intake manifold and the mixing is not completed at the mixer outlet (Supee, Shafeez, et al., 2014). Therefore, there is a need for analytical study of SFPMC mixer to work with 3.168 liter diesel engine.

## 1.3 Objectives

The objectives of this study are:

1. To examine the performance of existing secondary fuel pre mixing controller (SFPMC) commercial mixer in terms of AFR and CNG-air mixture homogeneity (CAMH).
2. To improve the design of the mixer by:
  - (a) Provide a homogeneous CNG-air mixture by keeping uniformity index (UI) of methane mass fraction ( $M_{\text{CH}_4}$ ) at the outlet of new mixer higher than 85% at various engine speeds and various AFRs.
  - (b) Design two new mixers in terms of controlling AFR; one with control valve (assuming the gas flowrate is mechanically controlled), and one without control valve (assuming the gas flowrate is electronically controlled).

## 1.4 Scope

The scope of the study is as follows:

1. SFPMC mixer is designed for 4-cylinders, 4-stroke, and 3.168 liter capacity diesel engine.
2. Engine operating at steady state with varied engine speeds 1000, 1500, 2000, 3000, and 3600 rpm.
3. Various AFR operations from rich (AFR = 10), to stoichiometric (AFR = 17.2) and to lean (AFR = 20, 30, and 40).
4. Initial mixer dimensions are taken from real commercial mixer.
5. Design two new mixers; one with control valve (to control gas flowrate mechanically), and one without control valve (to control gas flowrate electronically).
6. Using computational fluid dynamics (CFD) as analysis tool to investigate the performance of the mixer.
7. Since this study is focused on the fluid flow pattern inside the mixer, control valve mechanism (in mixer with control valve) and the flow controller (in mixer without control valve) are not a part of this study.

## 1.5 Significance of research

From the two primary objectives of study, the designed and best modified CNG-air mixer for DDF engine will be presented and selected. This mixer provides a homogeneous mixture of CNG and air with required AFR. Moreover, this mixer does not reduce air intake manifold to avoid engine power drop.

The correct strategies in this research to obtain the best design of the mixer in term of mixing homogeneity could be followed as a guide for mixer design. Furthermore, controlling gas flowrate mechanically by modified CNG-air mixer could be used as a guide for designing fluids flow control systems.

In addition, this research summarizes the techniques of using CFD simulation results to visualize and quantify of mixing homogeneity level of the mixture components.

## 1.6 Thesis Organization

Chapter 2 reviews the literature on the diesel dual fuel engine, characteristics of CNG as alternative fuel, the effects of AFR and mixture homogeneity on the engine performance, methods to show and quantify mixture homogeneity, types of CNG-air mixer and its performance in terms of AFR and homogeneity of CNG-air mixture, and finally the use of CFD as an analysis tool.



Chapter 3 describes the methodology used to model and modify the design of SFPMC real commercial mixer, and the setting up of the simulation software (ANSYS FLUENT) to examine the original mixer and the suggested alternative designs in terms of AFR and homogeneity of CNG-air mixture.

Chapter 4 presents the results and discussions on the effect of mixer design on AFR and the homogeneity of CNG-air mixture (HCAM). It begins by showing the effect of the original mixer design on the AFR and mixture homogeneity. After that, this chapter shows the comparison between the original mixer and the 10 suggested alternative designs in terms of CNG-air mixture homogeneity. Then, this chapter shows the results of a comparison between original mixer and the best two designs in terms of AFR and CNG-air mixture homogeneity.

Chapter 5 provides the general conclusions and the recommendations for future related studies.

## REFERENCES

- Abagnale, C., Cameretti, M. C., De Simio, L., Gambino, M., Iannaccone, S., & Tuccillo, R. (2014). Combined numerical-experimental study of dual fuel diesel engine. *Energy Procedia*, 45, 721-730.
- Abo-Serie, E., Özgür, M., & Altınışık, K. (2015). Computational Analysis of Methane-Air Venturi Mixer for Optimum Design.
- Agency, I. E. (2011). *World Energy Outlook* (978 92 64 12413 4). [https://www.iea.org/publications/freepublications/publication/WEO2011\\_WEB.pdf](https://www.iea.org/publications/freepublications/publication/WEO2011_WEB.pdf)
- Al-Saadi, A., Abdulwahab, A., & Bin Aris, I. (2015). *CNG-diesel dual fuel engine: A review on emissions and alternative fuels*. Paper presented at the Control Conference (ASCC), 2015 10th Asian.
- Anil, T., Ravi, S., Shashikanth, M., Tewari, P., & Rajan, N. (2006). *CFD Analysis of a Mixture Flow in a Producer Gas Carburetor*. Paper presented at the International Conference On Computational Fluid Dynamics, Acoustics, Heat Transfer and Electromagnetics CFEMATCON-06.
- Aslam, M., Masjuki, H., Kalam, M., Abdesselam, H., Mahlia, T., & Amalina, M. (2006). An experimental investigation of CNG as an alternative fuel for a retrofitted gasoline vehicle. *Fuel*, 85(5), 717-724.
- Azad, A. K., Uddin, S. M. A., & Alam, M. M. (2012). a Comprehensive Study of Di Diesel Engine Performance With Vegetable Oil: As Alternative Bio-Fuel Source of Energy. *International Journal of Automotive and Mechanical Engineering*, 5(June), 576-586.
- Badr, O., Karim, G., & Liu, B. (1999). An examination of the flame spread limits in a dual fuel engine. *Applied Thermal Engineering*, 19(10), 1071-1080.
- Bedoya, I. D., Arrieta, A. A., & Cadavid, F. J. (2009). Effects of mixing system and pilot fuel quality on diesel–biogas dual fuel engine performance. *Bioresource technology*, 100(24), 6624-6629.
- Bergman, T. L., Incropera, F. P., & Lavine, A. S. (2011). *Fundamentals of heat and mass transfer*: John Wiley & Sons.

Bora, B. J., Debnath, B. K., Gupta, N., Sahoo, N., & Saha, U. (2013). Investigation on the flow behaviour of a venturi type gas mixer designed for dual fuel diesel engines. *Int. J. Emerging Technol. Adv. Eng*, 3(3).

Cedigaz. (2014). Annual Surveys 2014-Natural Gas in the World 2014. <http://www.cedigaz.org/>

Chaichan, M. T. (2014). Combustion of Dual Fuel Type Natural Gas/Liquid Diesel Fuel in Compression Ignition Engine.

Chang, Y. S., Yaacob, Z., & Mohsin, R. (2007). Computational Fluid Dynamics Simulation of Injection Mixer for CNG Engines: WCECS.

Chintala, V., & Subramanian, K. (2013). A CFD (computational fluid dynamics) study for optimization of gas injector orientation for performance improvement of a dual-fuel diesel engine. *Energy*, 57, 709-721.

Coffield, D., & Shepherd, D. (1987). Tutorial guide to Unix sockets for network communications. *Computer Communications*, 10(1), 21-29.

Dahake, M., Patil, S., & Patil, S. (2016). Performance and Emission Improvement through Optimization of Venturi Type Gas Mixer for CNG Engines.

Danardono, D., Kim, K.-S., Lee, S.-Y., & Lee, J.-H. (2011). Optimization the design of venturi gas mixer for syngas engine using three-dimensional CFD modeling. *Journal of mechanical science and technology*, 25(9), 2285-2296.

de Castro, J. A. S., de Oliveira, T. F., & Quintero, C. H. L. (2012). Numerical Analysis and Optimization of Mixers.

Devarajan, R., & Samykano, M. (2010). Evaluation of a two stroke compressed natural gas mixer design by simulation and experimental techniques.

Economides, M. J., & Wood, D. A. (2009). The state of natural gas. *Journal of Natural Gas Science and Engineering*, 1(1), 1-13.

Ehsan, M. (2006). Effect of spark advance on a gas run automotive spark ignition engine. *J. Chem. Eng*, 24(1), 42-49.

- Europe, N. (2014). Worldwide NGV statistics.  
<http://www.ngvaeurope.eu/worldwide-ngv-statistics>
- FLUENT, A. (2012a). 14.5 Theory Guide. ANSYS Inc., Canonsburg, PA.
- FLUENT, A. (2012b). 14.5 User's Guide FLUENT Inc., Lebanon, NH.
- Fotouhi, A., & Montazeri, G. M. (2011). An investigation on vehicle's fuel consumption and exhaust emissions in different driving conditions. *International Journal of Environmental Research*, 6(1), 61-70.
- Geankoplis, C. J. (1995). transport-processes-and-unit-operations.
- Global, N. (2013). Current Natural Gas Vehicle Statistics | NGV Global Knowledgebase. <http://www.iangv.org/current-ngv-stats/>
- Global, P. (2015). *BP statistical review of world energy*.  
<http://www.bp.com/content/dam/bp/pdf/energy-economics/statistical-review-2015/bp-statistical-review-of-world-energy-2015-full-report.pdf>
- Gorjibandpy, M., & Sangsereki, M. K. (2010). Computational investigation of air-gas venturi mixer for powered bi-fuel diesel engine. *World Academy of Science, Engineering and Technology*, 71.
- Guibet, J.-C. (1997). Fuels and Engines-Technology, Energy and Environment, Vol. 1 & 2. Technip, Paris, latest edition.
- Happel, J., & Brenner, H. (2012). *Low Reynolds number hydrodynamics: with special applications to particulate media* (Vol. 1): Springer Science & Business Media.
- Heywood, J. B. (1988). *Internal combustion engine fundamentals* (Vol. 930): McGraw-hill New York.
- Hirsch, C. (2007). *Numerical Computation of Internal and External Flows: The Fundamentals of Computational Fluid Dynamics: The Fundamentals of Computational Fluid Dynamics*: Butterworth-Heinemann.

- Hussein Adel Mahmood, N. M. Adam., B. B. Sahari and S.U. Masuri. (2016). Investigation On The Air-Gas Characteristics Of Air-Gas Mixer Designed For Dual Fuel-Engines. *International Journal of Control Theory and Applications*, 9(30), 195-216.
- Jayaratne, E., Ristovski, Z., Morawska, L., & Meyer, N. K. (2010). Carbon dioxide emissions from diesel and compressed natural gas buses during acceleration. *Transportation Research Part D: Transport and Environment*, 15(5), 247-253.
- Jemni, M., Kantchev, G., & Abid, M. (2012). Intake manifold design effect on air fuel mixing and flow for an LPG heavy duty engine. *International Journal of Energy and Environment*, 3(1), 61e72.
- Kakaei, A.-H., & Paykani, A. (2013). Research and development of natural-gas fueled engines in Iran. *Renewable and Sustainable Energy Reviews*, 26, 805-821.
- Kakaei, A.-H., Paykani, A., & Ghajar, M. (2014). The influence of fuel composition on the combustion and emission characteristics of natural gas fueled engines. *Renewable and Sustainable Energy Reviews*, 38, 64-78.
- Kamil, M., Rahman, M., & Bakar, R. A. (2011). Performance evaluation of external mixture formation strategy in hydrogen fueled engine. *Journal of Mechanical Engineering and Sciences*, 1, 87-98.
- Karavalakis, G., Hajbabaie, M., Durbin, T. D., Johnson, K. C., Zheng, Z., & Miller, W. J. (2013). The effect of natural gas composition on the regulated emissions, gaseous toxic pollutants, and ultrafine particle number emissions from a refuse hauler vehicle. *Energy*, 50, 280-291.
- Karim, G., & Khan, M. (1968). Examination of effective rates of combustion heat release in a dual-fuel engine. *Journal of Mechanical Engineering Science*, 10(1), 13-23.
- Karim, G. A. (1980). A review of combustion processes in the dual fuel engine-the gas diesel engine. *Progress in Energy and Combustion Science*, 6(3), 277-285.

- Khan, M. I., Yasmin, T., & Shakoor, A. (2015a). International experience with compressed natural gas (CNG) as environmental friendly fuel. *Energy Systems*, 6(4), 507-531.
- Khan, M. I., Yasmin, T., & Shakoor, A. (2015b). Technical overview of compressed natural gas (CNG) as a transportation fuel. *Renewable and Sustainable Energy Reviews*, 51, 785-797.
- Kim, J., Kim, H., Yoon, S., & Sa, S. (2008). Effect of intake valve swirl on fuel-gas mixing and subsequent combustion in a CAI engine. *International journal of automotive technology*, 9(6), 649-657.
- Kumar, D. (2012). *Studies on improvement of intake manifold for compressed natural gas engine*. THAPAR UNIVERSITY.
- Lata, D., Misra, A., & Medhekar, S. (2012). Effect of hydrogen and LPG addition on the efficiency and emissions of a dual fuel diesel engine. *International Journal of Hydrogen Energy*, 37(7), 6084-6096.
- Leap, A. (2013). Computational Fluid Dynamics (CFD). *Tips & Tricks: Estimating the First Cell Height for correct Y+*. <http://www.computationalfluidynamics.com.au/tips-tricks-cfd-estimate-first-cell-height/>
- Liu, J., Yang, F., Wang, H., Ouyang, M., & Hao, S. (2013). Effects of pilot fuel quantity on the emissions characteristics of a CNG/diesel dual fuel engine with optimized pilot injection timing. *Applied Energy*, 110, 201-206.
- Liu, J., Yao, A., & Yao, C. (2015). Effects of diesel injection pressure on the performance and emissions of a HD common-rail diesel engine fueled with diesel/methanol dual fuel. *Fuel*, 140, 192-200.
- Mahmood, H. A., Adam, N. M., Sahari, B., & Masuri, S. (2016). Investigation on the Air-Gas Characteristics of Air-Gas Mixer Designed for Bi-Engines. *International Journal of Applied Engineering Research*, 11(12), 7786-7794.
- Malaysia, G. (2016). *Safety Data Sheet, Natural Gas*. [http://www.gasmalaysia.com/images/download/safety-datasheet/NaturalGas-May2015\(Rev.5\).pdf](http://www.gasmalaysia.com/images/download/safety-datasheet/NaturalGas-May2015(Rev.5).pdf)



- Malenshek, M., & Olsen, D. B. (2009). Methane number testing of alternative gaseous fuels. *Fuel*, 88(4), 650-656. <http://dx.doi.org/10.1016/j.fuel.2008.08.020>
- Mardani, B. (2004). Development of Intake System for Improvement of Performance of Compressed Natural Gas Spark Ignition Engine. *Doctor of Philosophy of Engineering (Mechanical), Faculty of Mechanical Engineering, University Technology Malaysia*, 14.
- Maxwell, T. T., & Jones, J. C. (1995). Alternative fuels: emissions, economics, and performance.
- MM, N., & MRM, R. (2008). Design and Simulate Mixing of Compressed Natural Gas with Air in a Mixing Device.
- Mohamad, T. I., Yusoff, A., Abdullah, S., Jermy, M., Harrison, M., & Geok, H. H. (2010). The combustion and performance of a converted direct injection compressed natural gas engine using spark plug fuel injector. *SAE Technical Paper*, 32-0078.
- Mohsin, R., Yaacob, Z., & Y., C. (2008). Review of mixture formation unit for CNG motorcycle. *Journal of Chemical and Natural Resources Engineering*, 1-7.
- N. Kapilan. (2010). Improvement of performance of dual fuel engine operated at part load. *International Journal of Automotive and Mechanical Engineering (IJAME)*, 2, 200-210.
- Nejadkoorki, F., & Baroutian, S. (2011). Forecasting extreme PM10 concentrations using artificial neural networks. *International Journal of Environmental Research*, 6(1), 277-284.
- Noor, M., Kadirgama, K., Devarajan, R., Rejab, M., Zuki, N., & Yusaf, T. (2008). *Development of a high pressure compressed natural gas mixer for a 1.5 litre CNG-diesel dual engine*. Paper presented at the Proceedings of the National Conference on Design and Concurrent Engineering (DECON) 2008.
- Pace, S., & Zho, G. (2009). Air-to-fuel and dual-fuel ratio control of an internal combustion engine. *SAE Int. J. Eng*, 2(2), 245-253.

- Pang, J. X., Qu, D. W., Lu, X., & Liu, G. Y. (2013). *Experimental Research on the Effect of Excess Air Ratio on Turbocharged Lean-Burned CNG Engine*. Paper presented at the Advanced Materials Research.
- Papagiannakis, R., & Hountalas, D. (2003). Experimental investigation concerning the effect of natural gas percentage on performance and emissions of a DI dual fuel diesel engine. *Applied Thermal Engineering*, 23(3), 353-365.
- Papagiannakis, R., & Hountalas, D. (2004). Combustion and exhaust emission characteristics of a dual fuel compression ignition engine operated with pilot diesel fuel and natural gas. *Energy conversion and management*, 45(18), 2971-2987.
- Papagiannakis, R. G. R., Kotsiopoulos, P. N. P., Zannis, T. C., Yfantis, E. a., Hountalas, D. T., & Rakopoulos, C. D. (2010). Theoretical study of the effects of engine parameters on performance and emissions of a pilot ignited natural gas diesel engine. *Energy*, 35(2), 1129-1138.
- Parra-Santos, T., Pérez-Domínguez, J., Szasz, R.-Z., & Castro-Ruiz, F. (2015). An isothermal analysis of curved-vane and flat-vane swirlers for burners. *Engineering Computations*, 32(3), 668-686.
- Pulkrabek, W. W. (2004). *Engineering fundamentals of the internal combustion engine* (Vol. 249): Pearson Prentice Hall New Jersey.
- Ramasamy, D. (2006). *Development of a compressed natural gas (CNG) mixer for a two stroke internal combustion engine*. (Masters of Engineering), Universiti Teknologi Malaysia. (TP761.C65 D48 2006)
- Reddy, R., & Reddy, P. (2014). Analysis of Producer Gas Carburetor for Different Air-Fuel Ratios Using CFD. *Journal of Research in Engineering and Technology*, 3.
- Sahoo, B., Sahoo, N., & Saha, U. (2009). Effect of engine parameters and type of gaseous fuel on the performance of dual-fuel gas diesel engines-A critical review. *Renewable and Sustainable Energy Reviews*, 13(6), 1151-1184.
- Saidur, R., Jahirul, M., Moutushi, T., Imtiaz, H., & Masjuki, H. (2007). Effect of partial substitution of diesel fuel by natural gas on performance parameters of a four-cylinder diesel engine. *Proceedings of the Institution of Mechanical Engineers, Part A: Journal of Power and Energy*, 221(1), 1-10.



- Sera, M. A., Bakar, R. A., & Leong, S. K. (2003). *CNG engine performance improvement strategy through advanced intake system* (0148-7191). Retrieved from
- Sharma, H., Singh, S., & Goel, R. (2014). CFD analysis of the natural gas based carburetor for a two stroke spark ignition engine. *Int. J. Mech. Eng. & Rob. Res.*
- Srinivas, K., & Fletcher, C. (2002). *Computational techniques for fluid dynamics: a solutions manual*: Springer Science & Business Media.
- Srinivas, K., & Fletcher, C. A. J. (1992). *Computational Techniques for Fluid Dynamics*.
- Stelmasiak, Z. (2004). Combustion with low NO<sub>x</sub> and smokeless in a dual-fuel diesel engine fuelled with natural gas as main fuel. *Journal of KONES Internal Combustion Engines*, 11(3-4).
- Supee, A., Mohsin, R., Majid, Z., & Raiz, M. (2014). Effects of Compressed Natural Gas (CNG) Injector Position on Intake Manifold towards Diesel-CNG Dual Fuel (DDF) Engine Performance. *Jurnal Teknologi*, 70(1).
- Supee, A., Shafeez, M., Mohsin, R., & Majid, Z. (2014). Performance of Diesel-Compressed Natural Gas (CNG) Dual Fuel (DDF) Engine via CNG-Air Venturi Mixjector Application. *Arabian Journal for Science and Engineering*, 39(10), 7335-7344.
- SUTAR, M. P. (2015). *Cfd Optimization of Venturi Mixer Design in Bi-Fuel Gas Engines*. Paper presented at the IRF International Conference. [http://iraj.in/up\\_proc/pdf/138-143020187105-09.pdf](http://iraj.in/up_proc/pdf/138-143020187105-09.pdf).
- United States Environmental Protection, A. (2007). *Automobile Emissions: An Overview*. <https://www3.epa.gov/otaq/consumer/05-autos.pdf>
- Versteeg, H. K., & Malalasekera, W. (2007). *An introduction to computational fluid dynamics: the finite volume method*: Pearson Education.
- Vongsateanchai, S., Rakdee, C., Vinaisompan, W., & Seanglum, N. (2011). Secondary Fuel Premixing Controller for an Air Intake Manifold of a Combustion Engine: Google Patents.

- Wei, L., & Geng, P. (2016). A review on natural gas/diesel dual fuel combustion, emissions and performance. *Fuel Processing Technology*, 142, 264-278.
- Wei, L., Yao, C., Wang, Q., Pan, W., & Han, G. (2015). Combustion and emission characteristics of a turbocharged diesel engine using high premixed ratio of methanol and diesel fuel. *Fuel*, 140, 156-163.
- Weltens, H., Bressler, H., Terres, F., Neumaier, H., & Rammoser, D. (1993). *Optimisation of catalytic converter gas flow distribution by CFD prediction* (0148-7191).
- Yaacob, Z., & Abdul Majid, Z. (1998). Natural gas motorcycle.
- Yaacob, Z., Majid, Z. A., Piau, M. P. K. L., & Long, O. H. (1999). A study on exhaust emission, performance and lubricating oil effects on natural gas motorcycle.
- Yeap Beng Hi, A. b. M., Zulkefli bin Yaacob. (2001). Computational Investigation of Air-fuel Mixing System for Natural Gas Powered Motorcycle: Universiti Teknologi Malaysia. Malaysia: M. Eng.
- Yusaf, T., Baker, P., Hamawand, I., & Noor, M. (2013). Effect of compressed natural gas mixing on the engine performance and emissions. *International Journal of Automotive and Mechanical Engineering*, 8, 1416-1429.
- Yusaf, T., & Yusoff, M. Z. (2000). *Development of a 3D CFD model to investigate the effect of the mixing quality on the CNG-diesel engine performance*. Paper presented at the Proceedings of the International Conference and Exhibition and Natural Gas Vehicles.
- Yusaf, T. F., Buttsworth, D., Saleh, K. H., & Yousif, B. (2010). CNG-diesel engine performance and exhaust emission analysis with the aid of artificial neural network. *Applied Energy*, 87(5), 1661-1669.

## BIODATA OF STUDENT

Hassan Sadah Muhssen was born on 13<sup>th</sup> September 1985 in Wasit province, Iraq. He completed primary school in the Al-Nuhuth primary school (1991-1996), intermediate school in Al-Shuhada intermediate school (1997-1999), and secondary school in Al-Muthanna secondary school (2000-2003). Then he was admitted to Middle Technical University, engineering technical college-, Baghdad to pursue his bachelor degree in the Department of automobiles technology. He graduated from the technical college in 2007 and was among the top ten students of the graduating class in 2007 from the Department of automobiles technology. Following his graduation he worked on contract in Wasit province until he took a government job in Wasit University in 2010. In 2013 he was admitted to Universiti Putra Malaysia for a master's degree in the Faculty of Engineering, Department of Mechanical and Manufacturing Engineering. Prior to his degree study he attended an English language course at the ELS Language Centers and later took some courses in addition to working on his thesis under the supervision of Dr. Siti Ujila Binti Masuri. His thesis focused on the numerical analysis (simulation) of performance investigation and design improvement of CNG-air mixer for dual fuel diesel vehicles.

## LIST OF PUBLICATIONS

Hassan S. Muhssen, S.U. Masuri, B.B Sahari, A.A. Hairuddin, Computational Fluid Dynamics Investigation of Air-Gas Pre Mixing Controller Mixer Designed For CNG-Diesel Dual-Fuel Engines. (Submitted to: International Journal of Automotive and Mechanical Engineering (IJAME)).

Submitted Patent under the Title of Secondary Fuel-Air Mixer for Internal Combustion Engine and Fuel Burner. Application No: PI201703422





## UNIVERSITI PUTRA MALAYSIA

### STATUS CONFIRMATION FOR THESIS / PROJECT REPORT AND COPYRIGHT

ACADEMIC SESSION : \_\_\_\_\_

#### TITLE OF THESIS / PROJECT REPORT :

NUMERICAL SIMULATION OF MIXING CHARACTERISTICS OF CNG-AIR MIXER FOR DUAL-FUEL VEHICLE

NAME OF STUDENT : HASSAN SADAH MUHSSEN

I acknowledge that the copyright and other intellectual property in the thesis/project report belonged to Universiti Putra Malaysia and I agree to allow this thesis/project report to be placed at the library under the following terms:

1. This thesis/project report is the property of Universiti Putra Malaysia.
2. The library of Universiti Putra Malaysia has the right to make copies for educational purposes only.
3. The library of Universiti Putra Malaysia is allowed to make copies of this thesis for academic exchange.

I declare that this thesis is classified as :

\*Please tick (✓)

☐

**CONFIDENTIAL**

(Contain confidential information under Official Secret Act 1972).

☐

**RESTRICTED**

(Contains restricted information as specified by the organization/institution where research was done).

☐

**OPEN ACCESS**

I agree that my thesis/project report to be published as hard copy or online open access.

This thesis is submitted for :

☐

**PATENT**

Embargo from \_\_\_\_\_ until \_\_\_\_\_  
(date) (date)

**Approved by:**

\_\_\_\_\_  
(Signature of Student)  
New IC No/ Passport No.:

Date :

\_\_\_\_\_  
(Signature of Chairman of Supervisory Committee)  
Name:

Date :

[Note : If the thesis is **CONFIDENTIAL** or **RESTRICTED**, please attach with the letter from the organization/institution with period and reasons for confidentially or restricted. ]